



MQ POWER 3 PHASE GENERATORS

Features and Benefits

- Heavy duty 4-cycle, direct injection, turbocharged, charge air cooled diesel engine provides maximum reliability
- Brushless alternator reduces service and maintenance requirements
- Shock welding to steel frame for minimum vibration and extended service life.
- Weather-resistant steel housing for durability
- Sound-deadening enables operation as low as 62dBA full load at 23 ft.
- Automatic safety shutdown system monitors the water temperature, engine oil pressure, low coolant, low DEF, overspeed, and overcrank. Warning lights indicate abnormal conditions
- Fully covered power panel allows fast and convenient hookup for most applications including temporary power boxes, tools and lighting equipment. All are NEMA standard
- Meets EPA emissions standards
- Internal fuel tank with direct reading fuel gauges
- Illuminated, easy-to-read instrument panels
- Fully lockable enclosure for safe, unattended operation
- Fuel/water separator removes condensation from fuel for extended engine life!
- Transport options include trailers and wheel kits for complete mobility

SPECIFICATIONS

PART NUMBER	EL-GN125SSJU4I	EL-GN150SSJU4F	EL-GN25SSJU4F	EL-GN40SSKU4F	EL-GN45SSJU4F	EL-GN70SSJU4I
ENGINE	170.3hp John Deere	240hp John Deere	40.2hp Isuzu	48.3hp Kubota	65.7hp Isuzu	97.9hp John Deere
OUTPUT	125 Kva / 100 Kw	150 Kva / 120 Kw	25 Kva / 20 Kw	36 Kva / 28 Kw	45 Kva / 36 Kw	70Kva / 56 Kw
DIMENSIONS	49 x 120 x 73" (1.25 x 3 x 1.85 m)	51 x 138 x 69" (1.2 x 3.5 x 1.75 m)	31 x 71.65 x 49.6" (0.7 x 1.8 x 1.25 m)	37.4 x 36 x 53" (0.94 x 0.91 x 1.3 m)	37.4 x 84 x 61" (0.94 x 2.1 x 1.5)	37.4 x 105 x 68" (0.94 x 2.66 x 1.7 m)
WEIGHT (DRY)	5,137 lbs (2,330 kg)	6,615 lbs (3,000 kg)	1,797 lbs (815 kg)	2,250 lbs (1020 kg)	2,337 lbs (1,060 kg)	3,329 lbs (1,510 kg)
CUBE	248.4 ft ³ (0.004 m ³)	281 ft ³ (0.0046 m ³)	63.75 ft ³ (0.001 m ³)	41.3 ft ³ (0.0006 m ³)	111 ft ³ (0.0018 m ³)	154.5 ft ³ (0.0025 m ³)
FUEL CONSUMPTION	7.3 gph at full load	8.4 gph at full load	1.62 gph at full load	2.2 gph at full load	1.62 gph at full load	4.4 gph at full load
FUEL CAPACITY	168 gallons (636 L)	69 gallons (260 L)	26 gallons (98 L)	67.4 gallons (L)	79.2 gallons	103 gallons
DECIBELS AT 23 ft	70 dBA	66 dBA	65 dBA	61 dBA	66 dBA	65 dBA
FITS TRAILER	EL-GNTRLR125USH	EL-GNTRLR180XFH	EL-GNTRLR45H EL-GNTRLR25US	EL-GNTRLR45H	EL-GNTRLR45H	EL-GNTRLR70USH