

SENTINEL I

Part Number SW-SI
Rapid Response Inflatable Shelter

**WESTERN
SHELTER** SYSTEMS
ISO 9001:2008 Registered Company



This lightweight Sentinel shelter can be fully erected by one person in under 5 minutes. Its standard internal inflator allows for rapid inflation without the use of additional pumps or hoses. The speedy set up of this

durable inflatable makes it the perfect fit for rapid response scenarios. It features a removable floor, integrated LED lighting, and the modular design can be connected to multiple shelters.

Key Features and Benefits

- Can be deployed by 1-2 people in less than 5 minutes
- Removable vinyl floor maintains environmentally secure shelter and gives each unit more flexibility when used in the line of duty
- Roof vent caps significantly reduces condensation
- Framework design allows individual replacement of parts
- Flame retardant vinyl is UV resistant for long life, resists mildew and abrasion
- Integrated LED lighting

Standard Components

- Plug In & Go internal inflation system (Built into shelter frame)
- Pre-fitted docking zippers around doors
- Heavy-duty non-slip PVC coated removable floor
- Integrated LED lighting

Optional Equipment

- 4 windows, 3-way system
- 4 duct openings for HVAC unit entry
- Modular inflatable frame with double inflation deflation valves
- Expansion wall strips
- Vinyl repair kit
- Vinyl storage/transport bags
- Inflation adapter with compressed air

SENTINEL I

Part Number SW-SI

Rapid Response Inflatable Shelter



SW-SI Specifications NSN Pending

Part Number	Sentinel I SW-SI3W (white) SW-SI3O (orange)	Sentinel I-W SW-SIW3W (white) SW-SIW3O (orange)
Dimensions		
Footprint	15'1" x 13'1" (4.5 x 4 m)	15'1" x 19'4" (4.5 x 5.9 m)
Peak	9'2"	9'2"
Square Footage	172 ft ² (16 m ²)	258 ft ² (24 m ²)
Packaged Dimensions		
Tent	35 x 32 x 24" (89 x 82 x 61 cm)	43 x 32 x 24" (109 x 82 x 61 cm)
Stakes	Included	Included
Repair kit	Included	Included
Electrical inflator	Included « Plug in & go system »	Included « Plug in & go system »
Total Weight	156 lbs (70 kg)	172 lbs (78 kg)
Setup Time	3 min	4 min

Recommended Support Systems

Shelter Connecting Systems

Increase the footprint of your shelter system with rigid frame connectors and entryways

Electrical Distribution

Portable power and lighting to sustain your shelter complex

Climate Control

Air heating, cooling, purifying and dehumidifying

Water Distribution

Purification, storage, heating and distribution kits

Hygiene Systems

Field showers and toilet stations

Storage And Transport

Heavy-duty cases and customizable cargo trailers

Digital ID

Your logo or name custom printed on roofs and doors for easy identification

Anchoring Systems

Secure your shelter against high winds

Shelter Accessories

Beds, work stations, tables, seating and food prep



Flame resistant, polyester fabric cover with removable floor and pre-fitted guy lines.

