

This self-contained, propane-fired heating module offers a continuous, instant supply of hot water. Units come complete with heater, pre-plumbed water distribution manifold including one cold water inlet, 2-hot water outlets, and one cold water outlet.

Key Features and Benefits

- Propane fired heating module
- Provides continuous supply of hot water for any situation
- Self contained in powder-coated aluminum case for extra protection
- · Pre-plumbed water distribution manifold
- Quick-connect propane hose with regulator

Standard Components

- Heate
- Pre-Plumbed Water Distribution Manifold Includes 1 Cold Water Inlet, 2 Hot Water Outlets And
 1 Cold Water Outlet
- Ouick-Connect Propane Line With Regulator
- 45 Second Quick-Lite Primer Valve
- Powder Coated Aluminum Case

Optional Components

- Wheel Kit
- Termostatic Control System





WA-WHP Specifications NSN Pending

Dimensions	39.5 x 22.5 x 13.5"	(1 x 0.57 x 0.3 m)
Weight	77 lbs	(35 kg)
Cube	6.94 ft ³ .	(0.19 m ³⁾
Output	117,000 BTU	
Rate of Rise	1.90 GPM	100°F
Flow	Min. 0.5 GPM	Max. 4.2 GPM
Water Pressure	Min. 2.0 PSI	Max. 150 PSI



815 Conger St., Eugene, OR USA 541.344.7267 1.800.971.7201 sales@westernshelter.com www.WesternShelter.com ISO 9001:2008 Registered Company