POWER DISTRIBUTION KIT

Part Number WS-EDK50

Route Power From High-Amp Distribution Panel Directly To Each Shelter



ISO 9001:2008 Registered Company





Key Features and Benefits

- · Easily route power from high amp distribution panel to each shelter within a complex
- GFCI protected with UL outdoor listing for safe and reliable power
- · Weather-proof with individual circuit breakers for dependability
- · Available in 220 V

Standard Components

- Power Distribution Box
- Two 50' Power Cables
- · Six 50' Extension Cords
- Powder Coated Aluminum Storage Case



WS-EDK50 Specifications

Power Box	
Dimensions	14.5 x 21 x 11" (36.8 x 53 x 28 cm)
Weight	30 lbs (13.6 kg)
6 GFCI Protected Circuits	20 Amp 125 V
1 Protected Outlet	30 Amp 240 V
1 Feed Through	50 Amp 125/250 V
WS50A50 Power Cables	
50' 125/250 V	6/4 and 8/1 SOW Water Resistant
WS15A50 Extension Cords	
50' 110 V	Yellow Glow Flex Cord with LED Lighted Female End
Molded 3-Wire Plug	Moisture and Flame Resistant
UL/CL Listed	Meets OSHA Requirements
WS2060 Powder Coated Aluminum Storage Case	
Dimensions	28 x 34 x 21" (71 x 86 x 53 cm)

176 lbs

(80 kg)

 11.57 ft^3 (0.32m³)





MILITARY INDUSTRIAL FIRST RESPONDER MEDICAL HOMELAND SECURITY EVENTS

Weight

Cube