



## Features and Benefits

- Multi-Fuel – diesel, kerosene or JP-8 aircraft fuel
- High flow hot water delivery with +/- 1° holding temperature
- Self contained in powder-coated aluminum case
- Portable design with removable wheels and recessed lifting handles

## Components

- Water Connections: 2 Hot and 1 Cold water outlet with 1 water inlet
- 1 weather tight 120V, 60 Hz, 15 amp outlet
- 1 weather tight 120V, 60 Hz, 15 amp inlet
- 1 auxiliary 120V, 60 Hz, 15 amp connection
- Fuel Cell: 8 gallon tank with gauge
- Control Panel:
  - 2 hot water valves
  - 1 cold water valve
  - 1 water inlet valve
  - 1 water pressure/temperature gauge
  - Power on/off switch
  - Fuse holder and fuse panel light toggle switch
  - 1 weather tight 120V, 60 Hz 15 amp outlet and inlet
  - System power indicator light unit

## Specifications

Part Number	WSDWHM350		WSDWHM650	
Dimensions	48 x 24 x 26"	(121 x 61 x 66 cm)	48 x 28 x 24.5"	(121 x 71 x 63 cm)
Weight	370 lb	(168 kg)	435 lb	(197 kg)
Cube	16 ft <sup>3</sup>	(4.8 m <sup>3</sup> )	19 ft <sup>3</sup>	(5.8 m <sup>3</sup> )
Maximum Pressure	12 gallons/min	(45 L/min.)	16 gallons/min	(60.6 L/min.)
Maximum PSI	150		150	
Minimum Flow Rate	Min. 0.75 gallon/min		(2.9 L/min.)	
Fuel Options	Diesel, Kerosene and JP-8			
Burner/Coil Output	440,000 BTU (Max)			

